



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/758,033	01/10/2001	Nobuhiro Komata	SCEI 17.966	8282
<div>7590 04/10/2009 Katten Muchin Zavis Rosenman 575 Madison Avenue New York, NY 10022-2585</div>			<div>EXAMINER DHARIA, PRABODH M</div>	
			<div>ART UNIT 2629</div>	<div>PAPER NUMBER</div>
			<div>MAIL DATE 04/10/2009</div>	<div>DELIVERY MODE PAPER</div>

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	Application No. 09/758,033	Applicant(s) KOMATA, NOBUHIRO	
	Examiner PRABODH M. DHARIA	Art Unit 2629	

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 22 February 2008.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-36 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-36 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 10 January 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All    b) ☐ Some \*    c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |   |   |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)  | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date <u>10-01-2001</u> . | 6) <input type="checkbox"/> Other: _____  |

***Priority***

1. Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.
2. Applicant's petition to revive abandon application number 09758033 received on 02-22-2008 has been reviewed by USPTO legal petition department and petition has been approved and granted on 03-17-2009. The prosecution of the application number 09758033 has been reopened. Claims 1-36 are pending in this action.
3. **Status:** Please all the replies and correspondence should be addressed to examiner's new art unit 2629. Receipt is acknowledged of papers submitted 02-22-2008 under petition to revive abandon application, which, have been placed of record in the file. Claims 1-36 are pending in this office action.
4. Applicant is notified that this was same office action that was mailed on 10-15-2002 to applicant and abandoned on 06-09-2003 for applicant's failure to respond and during telephone interview on 07-19-2007 applicant's representative claimed that they never received the office action mailed on 10-15-2002 as correspondence address change was requested and applicant's representative did not know if the office action was mailed to the newly change of address requested.

***Information Disclosure Statement***

5. The information disclosure statement (IDS) submitted on 10-01-2001 is in compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure statement is being considered by the examiner.

***Claim Rejections - 35 USC § 102***

6. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in-

- (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effect under this subsection of a national application published under section 122(b) only if the international application designating the United States was published under Article 21(2)(a) of such treaty in the English language; or
- (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that a patent shall not be deemed filed in the United States for the purposes of this subsection based on the filing of an international application filed under the treaty defined in section 351(a).

7. Claims 1-5,8 are rejected under 35 U.S.C. 102(e) as being anticipated by Amano et al. (EP 0 922 431 A1).

Regarding Claim 1, Amano et al. teaches a setup method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step

Art Unit: 2629

wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values, a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

Regarding Claim 2, Amano et al. teaches a recording medium (Col. 14, Lines 33,34) on which is recorded a computer-readable and executable software program (Col. 14, Lines 33-37) a setup method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values, a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

Art Unit: 2629

Regarding Claim 3, Amano et al. teaches the corrected pressure-sensing value table or various corrected pressure-sensing values are stored in a storage unit provided internally in or external of the computer (5 of figure 5, Col. 14, Lines 29-32).

Regarding Claim 4, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values, a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

Regarding Claim 5, Amano et al. teaches the corrected pressure-sensing value table or various corrected pressure-sensing values are stored in a storage unit internal to or external to the computer (5 of figure 5, Col. 14, Lines 29-32).

Art Unit: 2629

Regarding Claim 8, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values, a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

### ***Claim Rejections - 35 USC § 103***

8. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

9. Claims 6,7 are rejected under 35 U.S.C. 103(a) as being unpatentable over Amano et al. (EP 0 922 431 A1) in view of Ogata et al. (6,402,616).

Regarding Claim 6, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values, a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17 Line 40 to Col. 18, Line 4).

However, Amano et al. fails to teach the computer system is an entertainment system.

However, Ogata et al. teaches the computer system is an entertainment system (Col. 1, Lines 66,67).



Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Ogata et al. in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 7, Ogata et al. teaches the system is an entertainment system (Col. 1, Lines 8-15).

10. Claims 9-33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Amano et al. (EP 0 922 431 A1) in view of Armstrong (6,347,997 B1).

Regarding Claim 9, Amano et al. teaches the correction means has a correction table for correcting the user pressure-sensing values (Col. 17, Lines 24-29).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 10, Amano et al. teaches the correction table is prepared based on a stipulated program (Col. 17, Line 40 to Col. 18, Line 4).

Regarding Claim 11, Amano et al. teaches the correction table is prepared based on predetermined calculations (Col. 5, Line 45 to Col. 6, Line 7).

Regarding Claim 12, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values, a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 13, Amano et al. teaches the correction means has a correction table for correcting the user pressure-sensing values to correspond to the pressure-sensing values based on the stipulated function (Col. 17, Line 40 to Col. 18, Line 4, Col. 5, Line 45 to Col. 6, Line 7).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 14, Amano et al. teaches the stipulated function is selected from a group consisting of second-order functions, higher-order functions, exponential functions and trigonometric functions, depending on characteristics of the instructions controlled by the control element (Col. 10, Line 4 to Col. 12 Line 34).

Regarding Claim 15, Amano et al. teaches the correction table is prepared based on a stipulated program (Col. 17, Line 40 to Col. 18, Line 4, Col. 5, Line 45 to Col. 6, Line 7).

Regarding Claim 16, Amano et al. teaches the correction table is prepared based on predetermined calculations (Col. 17, Line 40 to Col. 18, Line 4, Col. 5, Line 45 to Col. 6, Line 7).

Regarding Claim 17, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a

Art Unit: 2629

controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

However, Amano et al. fails to teach game pressure-sensing value rate of change set by the software, and correction means for making the maximum user pressure-sensing value rate of change to correspond to the maximum game pressure-sensing value rate of change, and calculating intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change; wherein the user pressure-sensing value rate of change which is a pushing speed of the user on the control element is corrected by the correction means and used in the software.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12) and game pressure-sensing value rate of change set by the software, and correction means for making the maximum user pressure-sensing value rate of change to correspond to the maximum game

Art Unit: 2629

pressure-sensing value rate of change, and calculating intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change; wherein the user pressure-sensing value rate of change which is a pushing speed of the user on the control element is corrected by the correction means and used in the software (Col. 4, Lines 34-61).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 18, Amano et al. teaches the stipulated function is selected from a group consisting of second-order functions, higher-order functions, exponential functions and trigonometric functions, depending on characteristics of the instructions controlled by the control element (Col. 10, Line 4 to Col.12, Line 34).

Regarding Claim 19, Amano et al. teaches the correction table is prepared based on a stipulated program (Col. 17, Line 40 to Col. 18, Line 4, Col. 5, Line 45 to Col. 6, Line 7).

Regarding Claim 20, Amano et al. teaches the correction table is prepared based on predetermined calculations (Col. 17, Line 40 to Col. 18, Line 4, Col. 5, Line 45 to Col. 6, Line 7).

Art Unit: 2629

Regarding Claim 21, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 22, Amano et al. teaches the correction means has a correction table for correcting the user pressure-sensing values (Col. 17, Lines 24-29).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 23, Amano et al. teaches the correction table is prepared based on a stipulated program (Col. 17, Line 40 to Col. 18, Line 4).

Regarding Claim 24, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (Col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34)to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines

Art Unit: 2629

27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 25, Amano et al. teaches the correction means has a correction table for correcting the user pressure-sensing values (Col. 17, Lines 24-29).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 26, Amano et al. teaches the correction table is prepared based on a stipulated function (Col. 17, Lines 3-5).

Regarding Claim 27, Amano et al. teaches the stipulated function is selected from a group consisting of second-order functions, higher-order functions, exponential functions and



Art Unit: 2629

trigonometric functions, depending on characteristics of the instructions controlled by the control element (Col. 10, Line 4 to Col.12, Line 34).

Regarding Claim 28, Amano et al. teaches the correction table is prepared based on a stipulated program (Col. 17, Line 40 to Col. 18, Line 4).

Regarding Claim 29, Amano et al. teaches the correction table is prepared based on predetermined calculations (Col. 5, Line 45 to Col. 6, Line 7).

Regarding Claim 30, Amano et al. teaches a computer system (Col. 14, Lines 27,28) comprising: pressure sensing controller (figure 5, Col. 14, Lines 14-26) setup a method for a controller (4 of figure 5, Col.14, Lines 27, 28) that gives instructions (Col. 14, Lines 33,34, Col. 17, Lines 5-11) to a computer running software (Col. 14, Lines 33,34) depending on a pushing pressure by a user (col. 17, Lines 8-10) on a control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

However, Amano et al. fails to teach game pressure-sensing value rate of change set by the software, and correction means for making the maximum user pressure-sensing value rate of change to correspond to the maximum game pressure-sensing value rate of change, and calculating intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change; wherein the user pressure-sensing value rate of change which is a pushing speed of the user on the control element is corrected by the correction means and used in the software.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12) and game pressure-sensing value rate of change set by the software, and correction means for making the maximum user pressure-sensing value rate of change to correspond to the maximum game pressure-sensing value rate of change, and calculating intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change; wherein the user pressure-sensing value rate of change which is a pushing speed of the user on the control element is corrected by the correction means and used in the software (Col. 4, Lines 34-61).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 31, Amano et al. teaches the correction means has a correction table for correcting the user pressure-sensing values (Col. 17, Lines 24-29).

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 32, Amano et al. teaches the correction table is prepared based on a stipulated program (Col. 17, Line 40 to Col. 18, Line 4).

Regarding Claim 33, Amano et al. teaches the correction table is prepared based on predetermined calculations (Col. 5, Line 45 to Col. 6, Line 7).

11. Claims 34-36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ogata et al. (6,402,616 B1) and Amano et al. (EP 0 922 431 A1) in view of Armstrong (6,347,997 B1).

Regarding Claim 34, Ogata et al. teaches a recording medium (figure 9,10, Col. 7, Line 48) on which is recorded a computer-readable and executable software program (Col. 8, Lines 22-30) containing a setup program (Col. 8, Lines 31-39) for a controller that gives instructions to a computer running software depending on a pushing pressure of a user on a control element (Col. 7, Line 54 to Col. 8, Line 4, Col. 8, Lines 18-25, Lines 14-17).

However, Ogata et al. fails to teach control element connected to a pressure-sensitive device of the controller, the setup program comprising the steps of: measuring a maximum user pressure-sensing value which is the maximum pushing pressure of the user; acquiring a

Art Unit: 2629

maximum game pressure-sensing value set by the software; and performing correction to make the maximum user pressure-sensing value to correspond to the maximum game pressure-sensing value, and calculate intermediate values until the maximum user pressure-sensing value is reached proportionally corresponding to the game pressure-sensing values.

However, Amano et al. teaches control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Amano et al. in the teaching of Ogata et al. to provide better entertainment system including a video game.

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 35, Ogata et al. teaches a recording medium (figure 9,10, Col. 7, Line 48) on which is recorded a computer-readable and executable software program (Col. 8, Lines 22-30) containing a setup program (Col. 8, Lines 31-39) for a controller that gives instructions to a computer running software depending on a pushing pressure of a user on a control element (Col. 7, Line 54 to Col. 8, Line 4, Col. 8, Lines 18-25, Lines 14-17).

However, Ogata et al. fails to teach control element connected to a pressure-sensitive device of the controller, the setup program comprising the steps of: measuring a maximum user pressure-sensing value which is the maximum pushing pressure of the user; acquiring a maximum game pressure-sensing value set by the software; and performing correction to make the maximum user pressure-sensing value to correspond to the maximum game pressure-sensing value, and calculate intermediate values until the maximum user pressure-sensing value is reached proportionally corresponding to the game pressure-sensing values.

However, Amano et al. teaches control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col.

Art Unit: 2629

17, Line 40 to Col. 18, Line 4) and pressure-sensing values based on a stipulated function (Col. 17, Lines 3-5).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Amano et al. in the teaching of Ogata et al. to provide better entertainment system including a video game.

However, Amano et al. fails to teach the game pressure-sensing values.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

Regarding Claim 36, Ogata et al. teaches a recording medium (figure 9,10, Col. 7, Line 48) on which is recorded a computer-readable and executable software program (Col. 8, Lines 22-30) containing a setup program (Col. 8, Lines 31-39) for a controller that gives instructions to a computer running software depending on a pushing pressure of a user on a control element (Col. 7, Line 54 to Col. 8, Line 4, Col. 8, Lines 18-25, Lines 14-17).

However, Ogata et al. fails to teach control element connected to a pressure-sensitive device of the controller, the setup program comprising the steps of: measuring a maximum user pressure-sensing value which is the maximum pushing pressure of the user; acquiring a maximum game pressure-sensing value set by the software; and performing correction to make the maximum user pressure-sensing value to correspond to the maximum game pressure-sensing value, and calculate intermediate values until the maximum user pressure-sensing value is reached proportionally corresponding to the game pressure-sensing values.

However, Amano et al. teaches control element connected to a pressure-sensitive device (Col. 12, Line 57 to Col. 13, Line 2, Col. 17, Lines 6-11) of the controller (Col. 14, Lines 27,28), the method, comprising: an instruction step wherein the user is instructed (Col. 17, Line 8, Line 34) to push the control element with at least a maximum strength (Col. 17, Lines 35,36), a storage step wherein a value obtained when the control element is pushed by the user, is stored as the maximum value (Col. 17, Lines 33-38); and a correction step wherein, based on the maximum value and a pressure-sensing value table defined in the software or various pressure-sensing values (Col. 17, Lines 51), a new corrected pressure-sensing value table (Col. 14, Lines 27-32, Col. 17, Lines 3-5) or various new corrected pressure-sensing values are generated (Col. 17, Line 40 to Col. 18, Line 4) and calculate intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change (Col. 17, Line 40 to Col. 18, Line 4).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Amano et al. in the teaching of Ogata et al. to provide better entertainment system including a video game.

However, Amano et al. fails to teach game pressure-sensing value rate of change set by the software, and correction means for making the maximum user pressure-sensing value rate of change to correspond to the maximum game pressure-sensing value rate of change, and calculating intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change; wherein the user pressure-sensing value rate of change which is a pushing speed of the user on the control element is corrected by the correction means and used in the software.

However, Armstrong teaches the games pressing sensor values (Col. 2, Lines 4-12) and game pressure-sensing value rate of change set by the software, and correction means for making the maximum user pressure-sensing value rate of change to correspond to the maximum game pressure-sensing value rate of change, and calculating intermediate values until the maximum user pressure-sensing value rate of change is reached proportionally corresponding to the game pressure-sensing value rate of change; wherein the user pressure-sensing value rate of change which is a pushing speed of the user on the control element is corrected by the correction means and used in the software (Col. 4, Lines 34-61).

Thus it would have been obvious to one in ordinary skill in the art at the time of invention was made to incorporate the teaching of Armstrong in the teaching of Amano et al. to provide better entertainment system including a video game.

### ***Conclusion***

8. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Brossard (6,302,790 B1) Audio visual output for a gaming device.

Shinohara et al. (6,422,943 B2) Game apparatus, game machine manipulation device, game system and interactive communication method foe game apparatus.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to PRABODH M. DHARIA whose telephone number is (571)272-7668. The examiner can normally be reached on M-F 8-30AM to 5PM.



The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Any response to this action should be mailed to:

Commissioner of Patents and Trademarks

Washington, D.C. 20231

/Prabodh M Dharia/

Primary Examiner,

Art Unit 2629

March 17, 2009